

INSTALLATION INSTRUCTIONS

REAR SIGNAL SPLITTER MODULE FOR INDIAN® SCOUT, 3-WIRE

2587 3-WIRE HARNESS

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

▲ WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

1

Cable Tie Mounts

1 Left Pigtail (black/blue/yellow) 8 Cable Ties

1 Right Pigtail (black/blue/gray) Alcohol Pad

YOU WILL ALSO NEED:

Metric socket set and ratchet or metric combination wrench set, cutting pliers, warm soapy water and clean rag, electrical tape

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

This module is intended for custom applications where the stock turn signals are removed and custom L.E.D. turn signals with 2 circuits: low brightness red run and high brightness red brake/turn functions are installed. Removal of the stock turn signals and any fabrication or adaption necessary to install custom turn signals is the responsibility of the customer.

- STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2 Remove the motorcycle's seat to gain access to the battery. Set the seat off to the side on a flat clean surface.
- STEP 3 Disconnect the battery ground terminal from the battery and set it off to the side. Disconnect the positive battery terminal from the battery and set it off to the side. Be sure the terminals are not near or touching the battery; or touching each other.
- STEP 4 Under the rear fender disconnect the electrical connectors of the tail light.
- STEP 5 Refer to PIC 1. Locate provided Harness and Left and Right Pigtails.

KURYAKYN.COM









INSTALLATION INSTRUCTIONS

REAR SIGNAL SPLITTER MODULE FOR INDIAN® SCOUT, 3-WIRE


-CONTINUED-

PIC 1 RIGHT PIGTAIL BLACK = GROUND RIGHT LIGHT BLUE = RUN YELLOW = RIGHT TURN & BRAKE 6-PIN PLUG/SOCKET CONNECTS TO TAIL LIGHT HARNESS 6-PIN PLUG * PIGTAILS CONNECT TO SIGNAL LIGHTS CONTROLLER **POWER (RED) WIRE 6-PIN SOCKET** RING TERMINALS **LEFT PIGTAIL** CONNECT TO BLACK = GROUND **BATTERY POSTS** BLUE = RUN GROUND (BLACK) WIRE **GRAY = LEFT TURN & BRAKE** WITH RING TERMINAL LEFT LIGHT **PLUG**

STEP 6 Position the provided Harness under the rear fender near the license plate assembly. Route the wires with the ring terminals attached to them along the stock harness inside of the rear fender, and through to the under-seat area. Set wires off to the side for now; be sure they are not near or touching the battery.

> Note: It is suggested to wait to tidy up and secure all wires after installation of all parts, thus allowing for adjustments to be made.

- STEP 7 Locate the rear tail light's disconnected electrical connectors, from Step 4, and connect the 6-pin connectors of the provided Harness to it.
- STEP 8 Refer to FIG 1. Locate new turn signals (sold separately). Determine which signal is the left and right. Splice the Left and Right Pigtails to their corresponding lights.
- STEP 9 Install new lights per the instructions provided with them. Connect pigtail connectors to corresponding connectors on the provided Harness.
- **STEP 10** Under the seat area fasten the Harness' power (red) wire, and the positive battery terminal, to the positive post of the battery.
- **STEP 11** Fasten the Harness' black (ground) wire, and the ground battery terminal, to the negative post of the battery. Fully secure wires to the battery. Turn on ignition and verify that all of the lights properly function.
- Secure the Harness' controller box neatly under the tail light or to the **STEP 12** license plate assembly.
- **STEP 13** Use the included Cord Keepers and Cable Ties to secure all wiring up and out of harm's way on the inside of the rear fender; ensure that the wiring is secured away from any moving parts, excessive heat or pinch points. Use warm soapy water and a clean rag, remove all dirt and debris from surface areas where Cable Tie Mounts are being placed. Allow the area to dry completely before applying mounts.
- **STEP 14** Ensure all of the lights properly function before operating the motorcycle.



KURYAKYN.COM







INSTALLATION INSTRUCTIONS

REAR SIGNAL SPLITTER MODULE FOR INDIAN® SCOUT, 3-WIRE

-CONTINUED-

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- 1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- 2. The product must be properly installed, maintained & operated under normal conditions.
- 3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
- 4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- 5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
- 6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that after the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM







