

INSTALLATION INSTRUCTIONS

DILLINGER LEVERS FOR '96-'17 CABLE CLUTCH, SILVER

6681

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Brake Lever
- 1 Clutch Lever

YOU WILL ALSO NEED:

Snap ring pliers, combination wrench set, hex bit set, in-lbs (Nm) torque wrench

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

WARNING A FACTORY SERVICE MANUAL WILL BE HELPFUL IN PERFORMING THIS INSTALLATION. DO NOT ATTEMPT TO PERFORM THIS INSTALLATION IF YOU ARE NOT CONFIDENT IN YOUR ABILITY TO COMPLETE ALL OF THE STEPS IN THE PROCEDURE; CONSULT A TRAINED TECHNICIAN. IMPROPER INSTALLATION COULD RESULT IN SERIOUS INJURY OR DEATH.

NOTICE AVOID DAMAGE TO THE MOTORCYCLE. PROTECT PAINTED SURFACES WITH A SOFT CLOTH OR BLANKET.

BRAKE SIDE

STEP 2 Remove the snap ring securing the brake (right-side) lever pivot pin. Set it aside, it will be reused.

STEP 3 Refer to PIC 2. Loosen, do not remove, the screws on the back of the brake switch housing, and the front of the switch housing clamp.

STEP 4 Remove the pivot pin. Set it aside, it will be reused.

STEP 5 Refer to PIC 3. Carefully remove existing brake lever from the master cylinder/lever assembly. Remove the OEM nylon bushing from the lever.



PIC 1



PIC 2



PIC 3

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM

454 COUNTY ROAD VV SOMERSET, WI 54025

INSTALLATION INSTRUCTIONS

DILLINGER LEVERS FOR '96-'17 CABLE CLUTCH, SILVER

6681

-CONTINUED-

- STEP 6** Locate provided Brake Lever. Insert the OEM nylon bushing into the top of the lever.
- STEP 7** Refer to PIC 4. Align and place the lever into the master cylinder/lever assembly. Be sure the bushing remains flush while installing the new brake lever, and that the brake switch and plunger are compressed as the lever is installed.
- STEP 8** Reinstall the pivot pin and secure it with the snap ring. Adjust the position of the master cylinder/lever assembly and tighten the switch housing and switch housing clamp screws.

TORQUE VALUE FOR SWITCH HOUSING CLAMP SCREWS:
60-80 IN-LBS (6.8-9 NM)
TORQUE VALUE FOR SWITCH HOUSING SCREWS:
35-45 IN-LBS (4-5.1 NM)

- STEP 9** Compress the Brake Lever a few times to ensure that the brakes and brake lights works properly BEFORE starting the motorcycle.

CLUTCH SIDE

- STEP 10** Remove the snap ring securing the clutch (left-side) lever pivot pin. Set it aside, it will be reused.
- STEP 11** Remove the pivot pin. Set it aside, it will be reused.
- STEP 12** Refer to PIC 5. Loosen the clutch cable adjuster so the maximum amount of slack is attained. Pull the cable housing as far out of the clutch perch as possible and rotate the cable and housing away from the handlebar. The lever may now be pulled free of the perch.
- STEP 13** Carefully remove the lever and clutch cable from the perch. Remove the clutch cable anchor pin from the lever, freeing the cable from the lever. Set the anchor pin aside, it will be reused.


- STEP 14** Refer to PIC 6. Carefully remove the clutch cable from the lever. Now is a good time to lube your clutch cable.

- STEP 15** Refer to PIC 7. Locate provided Clutch Lever. Insert the clutch cable clevis into the lever and fasten it in place using the OEM anchor pin.

PIC 4



PIC 5



PIC 6



PIC 7



KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM
454 COUNTY ROAD VV SOMERSET, WI 54025

INSTALLATION INSTRUCTIONS

DILLINGER LEVERS FOR '96-'17 CABLE CLUTCH, SILVER

6681

-CONTINUED-

STEP 16 Refer to PIC 8. Align and place the lever into the clutch perch. Reinstall the pivot pin and secure it with the snap ring.

STEP 17 Adjust the clutch cable so there is about 1/8" of free play in the lever. Carefully tighten the adjuster locknut. Replace the rubber boot or cover over the adjuster.

**TORQUE VALUE FOR CLUTCH CABLE ADJUSTMENT JAM NUT:
120 IN-LBS (13.6 NM)**

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice