

INSTALLATION INSTRUCTIONS

TAPERED PEG ADAPTERS FOR HONDA, SUZUKI, TRIUMPH & YAMAHA, CHROME

8802

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

▲ WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION AFFRET YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- Peg Adapters
- 1 Hardware Kit containing:
 - 2 10-32 x 3/8 Set Screws
 - 5/16-18 x 1 1/2 Button Head Cap Screws
- Hardware Kit, containing CONTINUED
 - 2 5/16-18 Nylon Inserts
 - .245 x .325 x .75 Spacers
 - "D" Spring Washers

YOU WILL ALSO NEED:

Set of hex wrenches, combination wrenches, locking pliers, drill, 1/4" drill bit, safety glasses

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

PROCEDURE FOR METRIC CRUISERS

STEP 2

Remove the hardware that is securing the stock peg on to the bike. Remove the stock peg. Set aside the stock hardware, it may be reused depending on the application.

STEP 3

Take the new peg adapter and determine if you will need to use the supplied spacer (see PIC. 3) to prevent excessive slack in the peg adapter. If you use the spacer (see PIC. 3), you will need to reuse your stock mounting hardware.

STEP 4

Some applications you will not need to use the spacer. If the spacer is not reused you can use the provided 5/16-18 x 1 1/2 Button Head Cap Screw mounting hardware.

STEP 5

Once you have determined the proper mounting hardware, put the 10-32 x 3/8 Setscrew in the back of the peg adapter.

STEP 6

Reinstall peg adapter on the bike and use the supplied "D" Spring Washer(s) to take up the remaining slack and to make the peg snug when put in an upright position.

STEP 7

Once on the bike you can turn-out the setscrew to raise the peg or turn-in the setscrew to lower the peg angle

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025











INSTALLATION INSTRUCTIONS

TAPERED PEG ADAPTERS FOR HONDA, SUZUKI, TRIUMPH & YAMAHA, CHROME

8802

-CONTINUED-

PROCEDURE FOR BIKES WITH RIVET STYLE HARDWARE

▲ CAUTION

LARGER FOOTPEGS MAY LIMIT CORNERING CLEARANCE.

STEP 2

Locate the area of the peg that needs to be drilled. See PIC. 1.

STEP 3

Wearing your safety glasses, use the drill and 1/4" drill bit to drill the rivet head off. See PIC. 2.

Note: You may need to hold the top side of the rivet with locking pliers to prevent the rivet from spinning.

STEP 4

With the rivet drilled out, remove the pin and slide the peg out of the

STEP 5

Install the new Footpeg Adapter with the provided hardware. Refer to PIC. 3 for location of hardware.

STEP 6

When you have the adapter tight, you can set the height of the peg by turning-in or turning-out the setscrew.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE, PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.







LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- 1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- 2. The product must be properly installed, maintained & operated under normal conditions.
- 3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
- 4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- 5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
- 6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kurvakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that after the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025







