

MOUNTING SUGGESTIONS:

Yamaha **Stryker 2011-15**

Tank Bib

Installation of Mustang tank bib:

- 1. Remove the seat and position the bib on the tank with the cutout around the dash
- 2. Thread the lower loop of elastic cord under the frame at the base of the tank, then stretch the loop wide and pull it forward over the latch bracket.
- 3. Rest the center of the larger elastic cord on the fuel cap. Route the cord under the front of both sides of the tank.
- 4. Pull the center of the cord back to the rear of the tank, guiding the cord under the tank.
- 5. Hook the center of the cord under the base of the tank securely. Be sure the cord is routed around the latch release cable as pictured.

the USA







6. Re-install the seat.

Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93221, 93222, 93353, 93354

You are cordially invited to - Tour the Mustang Factory-

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.