



Mounting Suggestions: Honda VTX 1800 C 2002-08 Two-Piece Seat

Hardware:

- Stock 6 mm Acorn Nut
- One Chrome Spool Washer (Included)
- One 1"x6 mm Bolt (Included)
- Two Nylon Washers (Included)



Baseplate Features:

The two-piece, marine-grade fiberglass baseplate is a direct replacement for the stock two-piece seat. Rubber bumpers are positioned to protect the frame and fender.

Stock Seat Removal Steps

1. Remove the Allen bolt on each side of solo with a 6 mm Allen wrench.
2. Remove the acorn nut at the rear of the seat with a 10 mm wrench.
3. Lift seat up and back to remove. Front and rear seat are bolted together.

Step 1



Step 2



Mounting Suggestions: Honda VTX 1800 C 2002-08 Two-Piece Seat

Mounting of Mustang Seat

1. Install one nylon washer under chrome spool washer and then secure to fender with 1"x6 mm bolt mounting hole on fender.
2. Mustang solo mounts just like stock: Slide nose bracket into frame under fuel tank.
3. Secure to frame using stock Allen bolts through side brackets.
4. Slide the passenger seat into spool washer under solo.
5. Use one nylon washer between rear chrome bracket and fender.
6. Secure using stock 6 mm acorn nut.

Step 1



Step 2



Step 5a



Step 5b



Step 4



Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref part #75900, 75901, 79270, 79271