## COBRA.

23801 E. La Palma Ave., Yorba Linda, CA 92887 Ph. 714.692.8180 Fax. 714.692.5016

Items Supplied >	Арр	lication >	www.cobrausa-vtwin.c
1 – MUFFLER ASSEMBLY 2 – 5/16 X 1/2 FLANGED HEX BOLT 1 - 268-65 MUFFLER CLAMP	HARLI		14-20 14-20
Instruction Manual >		: DOES NOT FIT STRI	EETROD 750. Page 1 of 1
Read all instructions carefully ar 1. Loosen the front and rear clamps on the c the heatshield down so the muffler clamp	atalytic converter heatsh	<b>installing your new</b> nield. Remove the rear	v slip-on mufflers
<ol> <li>Loosen the muffler clamp and remove the the headpipe.</li> </ol>		-	muffler backward off
3. Slide the supplied muffler clamp over the a facing inward and down.	slip-on muffler and positi	on it as shown in <b>Figu</b>	re 1 with the hex head
<ol> <li>Slide the muffler onto the headpipe until the Slide the muffler using the supplied mound catalytic converter heatshield and verify the single similar to the gap the stock muffler allot</li> </ol>	unting bolts in the same r nat the gap, where the m	manner as stock but <b>d</b>	
<ol> <li>Check all the clearances and alignments the clamps. (NOTE: The muffler clamp should the muffler clamp is slid forward past the st Tighten the mounting bolts to factory spect</li> </ol>	d be flush with the end of slots on the muffler slip th	the muffler when tight	ened. See Figure 1. If
7. IMPORTANT: Before starting your engine re exhaust system use a liquid based soap def clean water. Note: Avoid abrasive cleaning steel wool pads. Abrasives may breach the	tergent, such as dishwash methods such as granula	ing soap applied with a	soft cloth and rinse with
CLAMP SHOULD BE FLUSH WITH EDGE OF MUFFLER			
DO NOT SLIDE CLAMP PAST SLOTS HEX HEAD FACING			
FIGURE 1 INWARD AND DOWN	COBRA SLIP ON MUFFLER	FIGURE 2	CATALYTIC CONVERTER HEATSHIELD

RIDE LOUD ™