

MOUNTING SUGGESTIONS:

Suzuki M50 2005-2011 Solo and Passenger Seat

Hardware:	Solo: Chrome stud bracket White nylon washer Slotted nut	Passenger seat: Stock rear fender screw
Tools needed:	Metric Allen wrench 5/8″ wrench	

Removal of stock seat:

1. Remove the rear Allen screw. This will be used to mount your new Mustang seat.

2. Slide the passenger seat back to remove.

3. Remove the rear seat mounting bracket and handstrap.

4. Slide solo back and up to remove.

Installation of Mustang seat:





1. Install the stud bracket to the fender. The stud must be toward the back of the motorcycle. (If missing, this bracket is available as part 78122.)

2. Engage the solo's nose bracket into frame receptacle below tank. Place the nylon washer over the stud, lower the rear solo bracket over the stud, and secure with the slotted nut. Note: do not overtighten.

3. Engage the passenger seat's slotted front bracket with the slotted nut.

4. Secure the rear bracket with the stock screw.



Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to guestions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76590, 76591, 76592, 76593, 76594, 76595, 79540, 79541, 79542, 79543, 79544, 79545

You are cordially invited to Tour the Mustang Factory See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.