



EXTENDED GIRDER SHIFT LEVER 1026

FITS: HEEL OR TOE ON '83-UP ELECTRA GLIDES, ROAD GLIDES, STREET GLIDES, TOUR GLIDES, ROAD KINGS AND '86-UP FLST MODELS

PARTS INCLUDED

- 1 Extended Girder Shift Lever
1 5/16-18 X 3/4" Socket Head Cap Screw
1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Hex Keys, Large Standard Screwdriver

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

This lever is quite versatile and can be used to replace either the stock front or stock rear shift lever or both. It can also be used in conjunction with any of our Heel Shift Eliminators if "toe only" shifting is desired.

STEP 1 Use a Hex Key to remove the pinch bolt from the stock shift lever.

STEP 2 Make a mental note or measure the height of the stock lever to assist in positioning the new lever. Remove the stock lever from the splined shaft. It is sometimes helpful to use a large screwdriver to gently spread the lever to get it off the shaft.

STEP 3 Install a shift peg on the Extended Girder Shift Lever. It will accept any stock H-D shift peg or equivalent.



CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY
Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
• The product must be properly installed, maintained and operated under normal conditions.
• Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
• Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
• Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
• Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today--select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



NOTE: If re-using the stock shift peg, heating the exposed end of the stud with a small torch (i.e. Bernz-o-Matic) will break the thread locker bond and make removing the shift peg from the stock lever much easier.

STEP 4 Remove the pinch bolt from the Extended Girder Shift Lever and slide it onto the splined shaft. Sit on the bike and test the position of the lever. Make coarse adjustments by moving the lever up or down, one spline at a time. For now, don't worry if the position is not perfect.

STEP 5 Insert the pinch bolt, and tighten securely. Test the position of the lever. If it is not quite right, make fine adjustments by shortening or lengthening the shift linkage.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

Küryakyn[®]

Ride On!

PAGE

2

EXTENDED GIRDER SHIFT LEVER

INSTALLATION