

MOUNTING SUGGESTIONS:

Triumph Thunderbird 2009-2013

One-piece Seat

Hardware: Stock rear screw

Tools needed: 5mm Allen wrench

8mm wrench

Removal of Stock Seat:

- 1. Remove the 6mm rear screw from the fender with a 5mm Allen wrench.
- 2. Slide the passenger seat back, out of the fender bracket, and then up and off the fender.



- 3. Locate and remove the two solo seat side mounting bolts (slightly forward of the shocks) with a 5mm Allen wrench. These will not be needed to install your new Mustang seat.
- 4. Lift the rear of the solo up, and then back to remove from the motorcycle.

Installation of Mustang Seat:

 Remove the seat bracket from the fender with an 8mm wrench. Replace the bolts and washers into the fender and tighten securely.



2. Place the seat onto the frame and slide it forward, engaging the nose bracket into the receiver under the gas tank.

3. Install the stock 6mm rear screw through the rear seat bracket and into the fender. Tighten securely with a 5mm Allen wrench.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76837, 76838

You are cordially invited to - Tour the Mustang Factory-

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.